

Import Address Maintenance

This chapter covers the following topics:

- Import Address Maintenance Screen
- Return to Top of List
- Display Additional Address Information
- Erase Imported Addresses from Your Con-nect Node
- Unlink an Address
- Find Address

Import Address Maintenance Screen

The Import Address Maintenance function displays all addresses which have been imported to your Con-nect.

3:17 PM		* * * C O N - N E C T 3 * * *				26.Feb.98	
Cabinet LS		Import Address Maintenance				OLAP05	
Cmd	Addressee Name	CD Name	Alias	Mail Node	Last Date	Last Time	
---	-----	----	-----	-----	-----	-----	
—	AHA.SEATTLE	DAEFCOC	DjV	SEATTLE	13.02.1998	10:22	
—	ASHLEY.SEATTLE	DAEFCOC	Di0	SEATTLE	13.02.1998	10:22	
—	BINCAB.SEATTLE	DAEFCOC	Djf	SEATTLE	13.02.1998	10:22	
—	BLI.SEATTLE	DAEFCOC	DpV	SEATTLE	13.02.1998	10:22	
—	BJI.SEATTLE	DAEFCOC	DjZ	SEATTLE	13.02.1998	10:22	
—	BL.SEATTLE	DAEFCOC	DjU	SEATTLE	13.02.1998	10:22	
—	BR.BOSTON			BOSTON	09.02.1998	16:03	
—	Brinkmann.Cindy	DAEFCOC	D4U	SEATTLE	13.02.1998	10:22	
—	BSAC.SEATTLE	DAEFCOC	D4T	SEATTLE	13.02.1998	10:22	
—	CAB40.SEATTLE	DAEFCOC	DjW	SEATTLE	13.02.1998	10:22	
—	CRUISE.SEATTLE	DAEFCOC	Djh	SEATTLE	13.02.1998	10:22	
—	DBA.BOSTON			BOSTON	09.02.1998	16:03	
—	DBA.SEATTLE	DAEFCOC	DgK	SEATTLE	13.02.1998	10:22	
Cmd:				Position to _____			
TO Top		DI Display		UL Unlink		ER Erase	
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---							
Help		Menu		Quit		ErAll UlAll	
				Find		+ --	
Mark item(s) from the list above with a command or press a PF-key							

Addressee Name

Nickname created for the imported address based upon the import rules you specified with the Add Profile function. See *Add Profiles*.

CD Name

Name of central directory to which the address was uploaded.

Alias

A unique ID assigned to each address when uploaded to the central directory.

Mail Node

Name of Con-nect node from which the address originates, or the external mail node name.

Last Date

Date address was last imported to your Con-nect node.

Last Time

Time address was last imported to your Con-nect node.

Position to

You can enter a one or more characters to restart the list of addresses with the first address whose nickname begins with the character(s) you specified.

Return to Top of List

To reposition the address list to a selected addressee, you can enter TO in the Cmd column for the addressee and press ENTER. As a result, the selected addressee is now displayed at the top of the list.

Display Additional Address Information

To display the complete address of an addressee, you can enter DI in the Cmd column for the addressee and press ENTER.

2:33 PM	* * * C O N - N E C T 3 * * *		14.Feb.94
Cabinet LS	Address Maintenance - ESH.BOSTON		OLAN06
Mail Nickname for	BOSTON	BOSTON	
Last Name/Description	Eshberry	Initial	X
First Name	John		
Company	Walk America		
Title			
Department	Public Relations	Number	
Location			
Address	12004 Sunrise Valley Drive		
City	Boston		
Postal Code	20001	Country	USA
Phone	814-WAL-K000	Country Code	1
Extension	25		
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---			
HELP Menu ExtAd			
Press a PF-key			

The information displayed here is identical to that which is displayed when a Con-nect user issues the "DISPLAY Address name" command.

Once an address is imported to your Con-nect node, that address is an external address and additional address information is automatically created for the address. This information is a combination of the addressee's data and the external node's (the node from which the address originates) address information.

To display the additional address information, you can press PF4. As a result, as window similar to the one below is displayed:

2:33 PM	* * * C O N - N E C T 3 * * *		14.Feb.94
Cabinet LS	Address Maintenance - Display Address		OLAN06
Mail Nickname for	BOSTON	BOSTON	
Last Name/Description	Eshberry	Initial	X
First Name	John		
Company	Walk America		
Title	+-----+		
Department	!	Display Multinode Addressee	!
Location	!		!
Address	!	Node BOSTON__ User ESH_____	!
	!		!
	+-----+		
City	Boston		
Postal Code	20001	Country	USA
Phone	814-WAL-K000	Country Code	1
Extension	25		
Press a PF-key			

Erase Imported Addresses from Your Con-nect Node

You can erase imported addresses from your Con-nect node on an individual basis, or erase all imported addresses.

When you erase an imported address, that address will be automatically downloaded again if, at a later point in time, the Transaction counter for that address is higher than the MRD Transaction Counter on your node. This situation will occur, for example, if the address is modified on the address' originating node and then uploaded to the central directory. With the next download you perform this address is once again downloaded to your node.

Additionally, if you erase an imported address and, then, at a later date, decide that you need to import this address again (and the above situation has not occurred), you can force a download. To do so, you must reset the MRD Transaction Counter for the corresponding profile (for the address' originating node) and then perform a download.

To erase imported addresses on an individual basis, you mark each address with ER in the Cmd column and press ENTER. As a result, each address you marked is deleted from the "Import Address Maintenance" screen.

To remove *all* imported addresses from your Con-nect node, press PF4 to display the following window:

```

10:23 AM          * * * C O N - N E C T 3 * * *          14.Feb.94
Cabinet LS          Import Address Maintenance          OLAP05

Cmd Addressee Name      CD Name  Alias      Mail Node Last Date Last Time
---
_  AHA.SEATT +-----+ 94 10:22
_  ASHLEY.SE !          ! 94 10:22
_  BIN CAB.SE !          ! 94 10:22
_  BLI.SEATT !          ! 94 10:22
_  BJI.SEATT !  Erase all Imported Addresses          ! 94 10:22
_  BL.SEATTL !          ! 94 10:22
_  BR.BOSTON ! 106      Addresses will be erased.    ! 94 16:03
_  Brinkmann !          ! 94 10:22
_  BSAC.SEAT !  Enter Y to confirm: N          ! 94 10:22
_  CAB40.SEA !          ! 94 10:22
_  CRUISE.SE !          ! 94 10:22
_  DBA.BOSTO !          ! 94 16:03
_  DBA.SEATT !          ! 94 10:22
_  +-----+

Cmd:                                     Position to _____
TO Top  DI Display  UL Unlink  ER Erase
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---
      Help  Menu  Quit  ErAll UAll      Find  +  --
Press ENTER to continue

```

Enter *Y* to confirm the deletion and press ENTER.

When the erase procedure is completed, the addresses are deleted from the "Import Address Maintenance" screen and the total number of addresses erased is displayed.

To cancel the deletion, press ENTER.

Unlink an Address

You can unlink one, or all imported addresses to remove the directory synchronization address. When you unlink an address, any modifications which are made to the address data on the central directory are not applied to the imported address when the Download Addresses function is performed; it remains unchanged. However, the modified address is downloaded to your Con-nect node.

Notes:

1. With an imported address that has been unlinked, you can modify the address in cabinet SYSCNT just as with any address filed in cabinet SYSCNT.
2. Although an unlinked address is handled similar to an address which originates on your node, you cannot upload an unlinked address to the central directory.

To unlink an imported address, mark the imported address you want with UL in the Cmd column and press ENTER.

To unlink *all* imported addresses, press PF4 and enter *Y* in the resulting screen.

```

10:38 AM          * * * C O N - N E C T 3 * * *          14.Feb.94
Cabinet LS          Import Address Maintenance          OLAP05

Cmd Addressee Name      CD Name  Alias      Mail Node Last Date Last Time
-----
_  AHA.SEATT +-----+ 94 10:22
_  ASHLEY.SE !          ! 94 10:22
_  BINCAB.SE !          ! 94 10:22
_  BLI.SEATT !          ! 94 10:22
_  BJI.SEATT !  Unlink all Imported Addresses ! 94 10:22
_  BL.SEATTL !          ! 94 10:22
_  BR.BOSTON ! 104      Addresses will be unlinked. ! 94 16:03
_  Brinkmann !          ! 94 10:22
_  BSAC.SEAT ! Enter Y to confirm: N          ! 94 10:22
_  CAB40.SEA !          ! 94 10:22
_  CRUISE.SE !          ! 94 10:22
_  DBA.BOSTO !          ! 94 16:03
_  DBA.SEATT !          ! 94 10:22
_  +-----+

Cmd:                               Position to _____
TO Top  DI Display  UL Unlink  ER Erase
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10---PF11---PF12---
      Help Menu Quit ErAll UlAll      Find  +    --
Press ENTER to continue

```

In either case, the information in columns CD Name and Alias are deleted, as shown below.

Find Address

You can use an address' alias as a search qualifier to quickly position the list of addresses to that address. To do so, you press PF7 and enter the alias in the resulting window.

Note:

The search for an address' alias is case sensitive. This means that, for example, alias GhR must be entered as GhR and not ghr.

11:44 AM	* * * C O N - N E C T 3 * * *					14.Feb.94
Cabinet LS	Import Address Maintenance					OLAP05

Cmd	Addressee Name	CD Name	Alias	Mail Node	Last Date	Last Time
___	AHA.SEATT	+	-----+			94 10:22
___	ASHLEY.SE	!			! 94	10:22
___	BINCAB.SE	!			! 94	10:22
___	BLI.SEATT	!	Find a Particular Address Record by		! 94	10:22
___	BJI.SEATT	!	its Synchronization Address.		! 94	10:22
___	BL.SEATT	!			! 94	10:22
___	BR.BOSTON	!	Synchronization Address:		! 94	16:03
___	Brinkmann	!			! 94	10:22
___	BSAC.SEAT	!	Central Directory Name:	DAEFCOC_	! 94	10:22
___	CAB40.SEA	!	Alias:	_____	! 94	10:22
___	CRUISE.SE	!			! 94	10:22
___	DBA.BOSTO	!			! 94	16:03
___	DBA.SEATT	!			! 94	10:22

Cmd:		Position to _____	
TO Top	DI Display	UL Unlink	ER Erase
Enter-PF1---	PF2---	PF3---	PF4---
PF5---	PF6---	PF7---	PF8---
PF9---	PF10---	PF11---	PF12---
Help	Menu	Quit	ErAll U1All
Find	+	--	
Press ENTER to continue			